



# "ELEMENTS" – HEAVY CONTRACT USE WATER RESISTANT LVT

<b>Flooring Composition</b>	EN ISO 10582	Heterogen, 100% Virgin PVC (fully recyclable)	
<b>Surface Treatment</b>		PU	
<b>Size</b>	EN ISO 24342	Planks: 185 × 1228mm	Herringbone: 118 × 590mm
<b>Pack Size</b>		Planks: 2.73m <sup>2</sup>	Herringbone: 2.23m <sup>2</sup>
<b>Total Weight</b>	EN 430	Planks: 4.90kg/m <sup>2</sup>	Herringbone: 5kg/m <sup>2</sup>
<b>Total Thickness</b>	EN ISO 24346	2.50mm	
<b>Wear Layer Thickness</b>	EN ISO 24340	0.55mm	
<b>Micro-bevelled Edges</b>		4 × micro-bevels per plank	
<b>Embossing</b>		Realistic	
<b>Performance Classification</b>	EN ISO 10874	Class 23 / 34 / 42 Heavy Contract	
<b>Wear Group</b>	EN 660-2	Group T	
<b>Residual Indentation</b>	EN 433	Conforms	
<b>Reaction to Fire</b>	EN 13501-1	Bfl-s1	
<b>Sound Absorption</b>	EN ISO 140-8	5dB	
<b>Colour Fastness</b>	EN ISO 105 B02	6	
<b>Anti-slip Classification</b>	DIN 51130	R10 / 36+ Pendulum	
<b>Resistance to Chemicals</b>	EN 423	Unchanged*	
<b>Underfloor Heating Suitability</b>	Yes	To maximum temperature of 27°C (80.6F)	
<b>Castor Chair Test</b>	EN 425	Yes (type W – soft)	
<b>Emissions AgBB Z 156.603-1194</b>		Conforms	
<b>Phthalate Free</b>		Yes	
<b>Wear Warranty</b>		Lifetime residential / 15 year commercial	


Basket Weave




Diagonal Basket Weave




Brick




Herringbone





Double Herringbone



Diagonal Herringbone



\*during brief exposure to regular household products



PLANKS: 185 × 1228mm      HERRINGBONE: 118 × 590mm

## GENERAL

<b>Cleaning, maintenance and installation</b>	Please refer to guidance at <a href="http://www.elementslvt.co.uk">www.elementslvt.co.uk</a>
<b>Laying instructions</b>	We strongly recommend fitting is carried out by flooring professionals only and that advice is sought regarding the surface on which the LVT is to be laid and the correct adhesives to be used.
<b>Please note</b>	The Elements Collection has variations of colour between the planks to accentuate and enhance the unique character of real wood flooring, this has been developed to replicate the natural beauty of the wood designs. All warranties are subject to CCTUK T&C (available on request).
<b>Warranty</b>	Elements Realistic Embossed LVT is backed by our Lifetime Residential and 15 Year Commercial Warranty, subject to T&C available on request).

For a brochure, photos, warranty information and details on cleaning, maintenance and installation, please visit [www.elementslvt.co.uk](http://www.elementslvt.co.uk)



**Commercial Carpet Tiles UK**

[commercialcarpettilesuk.co.uk](http://commercialcarpettilesuk.co.uk)

Tel: 01793 317940 Email: [sales@cctuk.ltd](mailto:sales@cctuk.ltd)

Unit 5 Pagoda Park, Westmead Industrial Estate, Swindon, SN5 7UN